

7368 ISAM ONT G-140W-C

Residential ONT

The Nokia 7368 Intelligent Services Access Manager (ISAM) Optical Network Terminal (ONT) G-140W-C is the solution for home networking delivered by Gigabit Passive Optical Network (GPON). The device has built-in Wi-Fi® 802.11b/g/n/ac networking with triple play capability that simplifies the home equipment experience. It can provide triple play services with voice, video and data. The Nokia 7368 ISAM ONT G-140W-C is designed to take advantage of Nokia award-winning management platforms. These platforms include a customized Motive™ Home Device Manager that is integrated with the Nokia 5520 Access Management System (AMS) to deliver a uniform end-to-end operations, administration, and maintenance (OA&M) solution that carriers need to provide subscriber satisfaction.

Features

- Four RJ-45 10/100/1000 Ethernet ports with auto-negotiation and medium dependent interface/medium dependent interface crossover (MDI/MDIX) auto-sensing
- One plain old telephone service (POTS) port for carrier grade voice services
- Two USB 2.0 ports
- Wireless IEEE 2.4 GHz 802.11b/g/n 2 x 2 multiple input, multiple output (MIMO)
- Wireless IEEE 5 GHz 802.11ac 2 x 2 MIMO
- Built-in Layer 2 (L2) switch
- Forward error correction (FEC)
- Port forwarding
- Dynamic domain name system (DDNS)
- Network Address Translation/Network Address Port Translation (NAT/NAPT)
- Internet Group Management Protocol (IGMP) snooping and proxy



Benefits

- Integrates the ONT and wireless access point functions
- Delivers connectivity to the Ethernet and wireless devices within the home
- Supports triple play services with voice, video and high-speed internet access
- Supports IP video distribution
- Supports voice services using Session Initiation Protocol (SIP) with G.711, G.729
- Supports fax services
- Delivers video services efficiently with multicasting or unicasting
- IPsec and Layer 2 Tunneling Protocol (L2TP)

Technical specifications

Physical

- Height: 36 mm (1.4 in)
- Width: 170 mm (6.7 in)
- Depth: 125 mm (4.9 in)
- Weight: 0.3 kg (0.7 lb)
- Interface: 4 Gigabit Ethernet (GigE) + 1 POTS + 2 USB + Wi-Fi
- Wall or desk mounting
- Fiber management supported

Operating environment

- Temperature: -5°C to 45°C (23°F to 113°F)
- Relative humidity: 5% to 95%, non-condensing

Power

- Local powering with 12 V DC input using an external AC/DC adapter
- Input: 100-240 V AC, 50/60 Hz
- Output: 12 V DC, 1.5 A maximum
- Dying gasp
- Power consumption: <18 W

Safety and electromagnetic interference (EMI)

- Protection of over voltage/current
- K.21 compliance

GPON interfaces

- Compliant with G.984.2 Amd1, Class B+
- Receive sensitivity: -28 dBm
- Wavelength: 1490 nm downstream, 1310 nm upstream
- Line rate: 2.488 Gb/s downstream, 1.244 Gb/s upstream
- Wavelength blocking filter (WBF)
- GPON Encapsulation Method (GEM) mode support for IP/Ethernet service
- G.984.3 compliant FEC
- GEM port and T-CONT flexible mapping
- G.984.3 compliant dynamic bandwidth reporting (DBR)
- Serial number (SN), password and logical ONU ID (LOID) authorization
- G.984.3 compliant Advanced Encryption Standard (AES) in downstream
- Rogue ONT pattern (interoperability with Nokia optical line terminal [OLT])
- SC/APC connector

Ethernet

- Four 10/100/1000Base-T interfaces with RJ-45 connectors
- Ethernet port auto-negotiation or manual configuration
- MDI/MDIX automatically sense
- Virtual LAN (VLAN) tagging/detagging and marking/remarking of IEEE 802.1p per Ethernet port
- 1:1 VLAN/N:1 VLAN/VLAN transparent/QinQ VLAN
- Media access control (MAC) learning
- IGMP v2/v3 snooping, v2/v3 proxy

WLAN interfaces

- 802.11b/g/n
- 802.11ac
- WLAN on/off button
- 64/128 bits Wired Equivalent Privacy (WEP)



- Wi-Fi Protected Access (WPA) including WPA/WPA2, WPA-PSK/WPA2-PSK
- Wi-Fi Protected Setup (WPS)
- Wi-Fi Multimedia (WMM)
- 2 x 2 MIMO for 802.11b/g/n and 802.11ac
- Multiple service set identifiers (SSIDs)
- Application layer gateway (ALG) and UPnP
- Port forwarding
- Demilitarized zone (DMZ)
- DNS server/client and DDNS
- IPv4/IPv6 dual stack and DS Lite

USB interfaces

- Two USB 2.0 host interfaces
- External USB device data sharing using File Transfer Protocol (FTP)

POTS interfaces

- One FXS port for voice over IP (VoIP) service with RJ-11 connectors
- Multiple codecs: ITU-T G.711, ITU-T G.729 (A and B)
- SIP (RFC 3261)
- T.30/T.38 fax modes configurable
- G.168 echo cancellation
- Services: caller ID, call waiting, call hold, 3-way call, call transfer, message waiting indication
- Dual-tone multi-frequency (DTMF) dialing
- Balanced sinusoidal ring signal, 55 V root mean square (RMS)

Residential gateways

- Supports router/bridge hybrid mode for ONT
- Supports router or bridge mode on each UNI port
- Point-to-Point Protocol over Ethernet/Dynamic Host Configuration Protocol (PPPoE/DHCP) (server and client), static IP
- NAT/NAPT

Regulatory compliances

- CE Mark
- Wi-Fi Alliance

Quality of service (QoS)

- Ethernet port rate control
- 802.1p priority scheduling
- Strict priority (SP)/weighted round robin (WRR)/SP + WRR
- Broadcast/Multicast rate limiting

OA&M

- Supports OMCI/TR-069/WebGUI configuration
- Supports easy setup and smart alarm using WebGUI
- Alarm report and performance monitoring
- Remote software image download/activation/reboot over OMCI or TR-069
- Two software images backup and automatic rollback

Security

- Prevents denial of service (DoS), port scanning, ping of death
- MAC/IP/URL filter
- Firewall and access control list (ACL)

About Nokia

We create the technology to connect the world. Powered by the research and innovation of Nokia Bell Labs, we serve communications service providers, governments, large enterprises and consumers, with the industry's most complete, end-to-end portfolio of products, services and licensing.

From the enabling infrastructure for 5G and the Internet of Things, to emerging applications in digital health, we are shaping the future of technology to transform the human experience. networks.nokia.com

Nokia is a registered trademark of Nokia Corporation. Other product and company names mentioned herein may be trademarks or trade names of their respective owners.

© 2018 Nokia

Nokia Oyj
Karaportti 3
FI-02610 Espoo, Finland
Tel. +358 (0) 10 44 88 000

Document code: SR1802022099EN (March)